



## SX 50 FACTORY - TECHNICAL SPECIFICATIONS

<b>ENGINE</b>	Single cylinder, 2-stroke, liquid cooled
<b>DISPLACEMENT</b>	50 cc
<b>FRAME</b>	Steel perimeter frame
<b>FRONT SUSPENSION</b>	Ø 41 mm telescopic upside down fork
<b>REAR SUSPENSION</b>	Wheel travel: 240 mm Aluminium swingarm
<b>FRONT BRAKE</b>	Hydraulic monoshock absorber with linkage, wheel travel: 200 mm
<b>REAR BRAKE</b>	Ø 260 mm stainless steel disc with 2-piston floating calliper
<b>FRONT WHEEL</b>	Ø 220 mm stainless steel disc with floating calliper
<b>REAR WHEEL</b>	Lightweight alloy. Tyre 100/80 x 17
<b>SADDLE HEIGHT</b>	Lightweight alloy. Tyre 130/70 x 17
<b>FUEL TANK CAPACITY</b>	875 mm
<b>DRY WEIGHT</b>	7 lt
<b>WET WEIGHT</b>	94 kg
<b>EMISSIONS COMPLIANCE</b>	104 kg
<b>EMISSIONS</b>	Euro 4
<b>CONSUMPTION</b>	76 g/km (CO <sub>2</sub> )
<b>COLOUR RANGE</b>	3.14 l/100km
	Red Boost