



V7 III STONE – TECHNICAL SPECIFICATIONS

Engine	<i>Transversal 90° V-twin, two valves per cylinder.</i>
Cooling	<i>Air.</i>
Displacement	<i>744 cc.</i>
Bore x Stroke	<i>80 x 74 mm.</i>
Maximum power	<i>52 CV (38 kW) - 6.200 rpm (Also available at 35 kW, A2 driver license).</i>
Maximum torque	<i>60 Nm - 4.900 rpm.</i>
Compliance	<i>Meets European Directive Euro 4.</i>
Emissions	<i>128 g/km (CO2).</i>
Consumption	<i>5,5 l/100 km.</i>
Gearbox	<i>6 speed.</i>
Fuel tank	<i>21 l (4 reserve).</i>
Seat height.	<i>770 mm.</i>
Dry weight	<i>189 kg.</i>
Kerb weight	<i>209 kg (According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume).</i>
Front suspension	<i>Hydraulic telescopic fork Ø 40 mm.</i>
Rear suspension	<i>Swingarm Twin-sided with two spring preload adjustable shock absorbers.</i>
Front wheel	<i>Lightweight alloy, 18" 100/90 (18" 110/80 alternatives tyres).</i>
Rear wheel	<i>Lightweight alloy, 17" 130/80.</i>
Front brake	<i>Stainless steel floating disk Ø 320 mm, Brembo caliper with 4 differentiated and opposed pistons.</i>
Rear brake	<i>Stainless steel disk Ø 260 mm, floating 2 pistons caliper.</i>
Features	<i>MGCT Moto Guzzi Controllo di Trazione, Standard double channel ABS.</i>