

V7 III STONE NIGHT PACK – TECHNICAL SPECIFICATIONS	
Engine	Transversal 90° V-twin, two valves per cylinder.
Cooling	Air.
Displacement	744 cc.
Bore x Stroke	80 x 74 mm.
Maximum power	52 CV (38 kW) - 6.200 rpm (Also available at 35 kW, A2 driver license).
Maximum torque	60 Nm - 4.900 rpm.
Compliance	Meets European Directive Euro 4.
Emissions	128 g/km (CO2).
Consumption	5,5 l/100 km.
Gearbox	6 speed.
Fuel tank	21 I (4 reserve).
Seat height.	770 mm.
Dry weight	189 kg.
Kerb weight	209 kg (According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume).
Front suspension	Hydraulic telescopic fork Ø 40 mm.
Rear suspension	Swingarm Twin-sided with two spring preload adjustable shock absorbers.
Front wheel	Lightweight alloy, 18" 100/90 (18" 110/80 alternatives tyres).
Rear wheel	Lightweight alloy, 17" 130/80.
Front brake	Stainless steel floating disk Ø 320 mm, Brembo caliper with 4 differentiated and opposed pistons.
Rear brake	Stainless steel disk Ø 260 mm, floating 2 pistons caliper.
Features	Full LED lights package (headlamp, turn indicators, stop light), Short rear mudguard with integrated stop light mount, MGCT Moto Guzzi Controllo di Trazione, Standard double channel ABS.