



PIAGGIO®

BEVERLY 300 ABS ASR – TECHNICAL SPECIFICATIONS

| | |
|--|--|
| ENGINE | Single cylinder four-stroke |
| CAPACITY | 278 cc |
| BORE X STROKE | 75 mm x 63 mm |
| POWER | 15.5 kW (21 hp) at 7250 rpm |
| TORQUE | 25 Nm at 5750 rpm |
| DISTRIBUTOR | Four-valve single overhead camshaft |
| FUEL SUPPLY | Electronic injection |
| COOLING SYSTEM | Liquid |
| TRANSMISSION | CVT with torque server |
| FUEL CONSUMPTION (WMTC CYCLE) | 30.3 km / litre |
| CO² EMISSIONS | 78 g/km |
| EMISSION COMPLIANCE | Euro 4 |
| FRONT SUSPENSION | Hydraulic telescopic fork (35 mm) |
| REAR SUSPENSION | Double hydraulic shock absorbers with adjustable preload with 4 settings |
| FRONT BRAKE | 300-mm disc with dual piston floating calliper |
| REAR BRAKE | 240-mm disc with dual piston floating calliper |
| LENGTH / WIDTH | 2.190mm/780mm |
| WHEEL BASE | 1535mm |
| SEAT HEIGHT | 790mm |
| FUEL TANK CAPACITY | 12.5 litres |
| WEIGHT | 173.5 kg (dry) 183 kg (running order) |