

SPRINT – PRIMAVERA 125 (150) IGET ABS - TECHNICAL SPECIFICATIONS

ENGINE	3-valve 4-stroke single cylinder i-get catalysed
DISPLACEMENT	124 cc (155 cc)
BORE X STROKE	52 mm x 58,6 mm (58 mm x 58,6 mm)
MAX POWER AT THE CRANK SHAFT	8,1 kW - 11 HP - a 8,000 rpm (9,2 kW - 12,5 CV- 7,750)
MAX TORQUE	10.4 Nm at 6,750 rpm (12.4 Nm a 6,750 rpm)
CONSUMPTION	40 km/l (37 km/l)
CO2 EMISSIONS COMPLIANCE	60 g/km (63 g/km)
FUEL SYSTEM	Electronic Injection
COOLING	Forced air
STARTER	Electric
GEARBOX	CVT automatic with torque server
CLUTCH	Automatic dry centrifugal with shock absorbers
LOAD-BEARING STRUCTURE	Sheet steel shell with welded structural reinforcements
FRONT SUSPENSION	Single arm with helical spring and hydraulic shock absorber
REAR SUSPENSION	Helical spring with adjustable preload (4 positions) and single hydraulic shock absorber
FRONT BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
REAR BRAKE	Ø 140 mm drum with mechanical control
ABS/ASR SYSTEM	ABS at the front wheel only
FRONT TYRE	Tubeless 110/70 - 12"
REAR TYRE	Tubeless 120/70 - 12"
LENGTH/WIDTH/WHEELBASE	1.870 / 735 / 1.340 mm
SEAT HEIGHT	790 mm
FUEL TANK CAPACITY EMISSIONS COMPLIANCE	8 litres
EMISSION COMPLIANCE	Euro 5